

Main Frame & 3 Point linkage

Shovel

Harding Bush

Shear bolt protection



Features

- Sub Soiler is primary tillage deep plough working up to 55 cm depth approx.
- To ensure development of crop root system of proper depth and environment.
- The subsoiler increase natural fertility of soil as deep tillage provides enough circulation of air , moisture and sunlight into soil.
- It is an inexpensive implement and it provided a simple and economical way to obtain boosting crop yield.
- Depth can be adjusted by leg hole & top links .
- Shear bolt protection available in all sub soiler
- Adjustable width of ploughing available for sub-soiler.

Description	1 Tyne Sub Soiler	2 Tyne Sub Soiler	3 Tyne Sub Soiler
Main Frame Size mm	BOX Frame 100x100		
Type Mounting	Three Point Hitch Linkage (Cat II)"		
Overall length, mm	860	860	860
Overall Width, mm	850	1340	1450
Overall Height, mm	1470	1470	1470
Weight,(Kg)	165	225	300
Recommended Tractor Power (HP)	45 - 55	55 - 65	65 - 80
Working Depth range (mm)	550 (Depends On soil moisture and field condition)		
Tyne Size mm / Shovel Material	150 x 25 / EN8		

Note : Since product improvement is a continuous process, specifications & details provided are subject to change without prior information.

Bhansali Agricultural Implements Pvt. Ltd.

"Dhantara" Gurudwara Road, Kopargaon - 423601,
Ahmednagar District, Maharashtra, INDIA.

+91-2423-2233 91/92/93

info@bhansalitrailors.com

www.bhansaliagri.com